



## TECHNICAL DATA SHEET

### VACUUM BAGGING FILM 50UM

#### **Introduction**

VACUUM BAGGING FILM ARE USED TO EFFECTIVELY SEALS THE WHOLE OF THE AREA OF THE COMPOSITE LAMINATE TO BE CURED.

#### **Specification:**

MATERIALS	PA+PE+PA	
COLOR	YELLOW	
TEMPERATURE RESISTANCE	170°C	
ELONGATION	>400%	
TENSILE STRENGTH AT BREAK	LENGTH DIRECTION	>38MPA
	WIDTH DIRECTION	>35MPA
PUNCTURE	1.2N	
THICKNESS	50UM	
MAX WIDTH	8000MM	
ROLL LENGTH	AS PER CUSTOMER'S REQUIREMENTS	

Remark: Special products are available according to customer's requirement.

#### **Packing:**

The packing is according customer's requirement.

---

AMP Composites Co.,Ltd.

ADD:No.26 XingFa Road, LongXiang Industrial Area, TongXiang ZheJiang China  
314504

Tel: 0086 573 88793188 88792323 Fax: 0086 573 88793636

E mail: [sales@ampcomposites.com](mailto:sales@ampcomposites.com) Web: [www.ampcomposites.com](http://www.ampcomposites.com)